# Canon UNIVERSAL DATA SHEET

DATE: 03/03/10

| Item Code | Item Name |
|---|---|
| 3814B016 | EOS 7D EF-S 18-135 IS USM Kit |

Product Photo:

| Item | W | H | D | WEIGHT |
|---|---|---|---|---|
| Dimensions | 5.8 in | 4.4 in | 2.9 in | 28.92 oz. |

| Case Dimensions | Quantity | L | W | H | CUBIC FT. | WEIGHT |
|---|---|---|---|---|---|---|
| Unit Carton | 1 | 9.803 in | 7.205 in | 5.551 in | 0.227 c.ft. | 5.525 lb |
| Inner Carton | NA | | | | | |
| Master Carton | 6 | 17.362 in | 15.039 in | 11.339 in | 1.713 c.ft. | 35.098 lb |

| Item Description | Kit Includes |
|---|---|
| • 18MP CMOS sensor and Dual DIGIC 4 Imaging Processor for high image quality and speed | EOS 7D BODY |
| • ISO 100 – 6400 (expandable to12800) for shooting from bright to dim light | EF-S 18-135MM 1:3.5-5.6 IS USM |
| • 8.0 fps continuous shooting up to 126 Large/JPEGS with a UDMA CF card and 15 RAW | LENS CAP E-67 |
| • Advanced movie mode with manual exposure control and selectable frame rates: 1920 x 1080 (Full HD): 30p (29.97) / 24p (23.976) / 25p, 1280 x 1080 (HD): 60p (59.94) / 50p, 640 x 480 (SD): 60p (59.94) / 50p | LENS DUST CAP E |
| • Intelligent Viewfinder with 100% field of view, wide viewing angle of 29.4°, high magnification of 1.0x, intelligent viewfinder with glass penta-prism and superimposed LCD display in viewfinder supports various shooting styles. | EYECUP EG |
| • New all cross-type 19-point AF system equipped with dual diagonal cross-type sensors in center at f/2.8 and f.5.6 and AF area selections modes to match various shooting situations. | CAMERA COVER R-F-3 |
| • iFC metering with Multi-layer 63-zone metering sensor utilizes AF and color information for optimizing exposure and image quality. | WIDE STRAP EW-EOS7D |
| • 3" Clear View II LCD monitor, 160 viewing angle, 920,000-dot VGA, reflection resistance with multi coating and high-transparency materials for bright and clear viewing | BATTERY CHARGER LC-E6 |
| • Dual-axis electronic level for composition alignment. | BATTERY PACK LP-E6 |
| • Magnesium body with shutter durability up to 150,000 and exclusive dust-and-weather resistance | STEREO AV CABLE AVC-DC400ST |
| • New ergonomic design with high-quality coating for tactile feel and comfortable grip for better control | INTERFACE CABLE IFC-200U |
| • Compatible with full line of Canon EF and EF-S lenses | EOS DIGITAL SOLUTION DISK VER. 22.2 |
| | CAMERA INSTRUCTION BOOK (E/S) |
| | SOFTWARE INSTRUCTION BOOK CD |
| | POCKET GUIDE (E/S) |
| | CD-ROM GUIDE |
| | ACC PROMOTIONAL CD |
| | BARCODE LEAFLET OF DOCUMENT PACK NO. |
| | LEAFLEFT OF DIGITAL LEARNING CENTER WEBSITE |
| | CAMERA WARRANTY CARD (NA) |
| | LENS WARRANTY CARD (NA) |

| UPC Code | Mater Carton Code (SCC14) | Inner Carton Code (If Any) |
|---|---|---|
| 0 13803 11755 4 | 10 0 13803 11755 1 | |

| Warranty | | Country of Origin | Batt. Req? | Included Battery | Batt. Qty | UL # |
|---|---|---|---|---|---|---|
| LENGTH | TYPE | Japan | Yes | LP-E6 | 1 | |
| NA | NA | | | | | |